



shandong lu young machinery co.,ltd

luyoungcncmachines.com

2 Axis Cnc Lathe Machine Precision 750mm Distance Between Centre

Our Product Introduction

For more products please visit us on luyoungcncmachines.com

Basic Information

- Place of Origin: SHANDONG
- Brand Name: cnc lathe machine
- Certification: CE
- Model Number: CK6150
- Minimum Order Quantity: 1/SET
- Price: \$9000-\$15000
- Packaging Details: non-fumigation wooden box
- Delivery Time: 30DAYS
- Payment Terms: T/T
- Supply Ability: 30/SET





Product Specification

- Precision: High Precision
- Number Of Axes: 2
- Cnc Or Not: Cnc
- Spindle Speed Ranges: 100~1600r/min
- Positioning Accuracy: 0.01
- Cnc Control: GSK Or FANUC
- Machine Dimension: 2/2.3*1.5*1.7
- Tool Post Stations: 6, 4, 8
- Bar Diameter: 95mm
- Tailstock Quill Taper: MT-#5
- Max Workpiece Length: 380mm
- Usage: Metal Turning Lathe
- Diameter Of Sleeve: 75mm



More Images



Product Description

2 Axes Precision CNC Lathe Machine With 750mm Distance Between Centres

Product Description



ck6150 Chinese CE Small Benchtop Horizontal CNC Lathe Machine is a high-precision, high-efficiency automated machine tools, the whole machine with integrated protection structure, beautiful appearance. Mainly used for complex shape parts or high precision parts processing, can automatically complete internal and external Round surface, conical cotton, round face, end face, a variety of threads, drilling, hinge, boring and other turning. The machine is tested in strict accordance with the inspection procedure. Each machine adopts laser interferometer to detect X and Z axis positioning accuracy and repeat positioning accuracy to ensure the accuracy and reliability of the machine.

Item	CK6150A	ck6150B
Max. swing dia. over bed	Φ500mm	Φ500mm
Max. swing dia. over cross slide	Φ280mm	Φ280mm

Processing length	750/1000/1500/2000mm	
Dia. of spindle	Φ82mm	
Spindle speed step	step-less	Three gear speed manual change,frequency conversion stepless
Spindle speed	14-1500 rpm	30-150,100-500, 320-1600rpm
Taper of spindle bore	1:20/Φ90	
Spindle nose	Type of spindle head D-8	
Tool holder	4 station electric tool post	
Tool bar section	25X25mm	
Main motor power	7.5KW	
X/Z axis position accuracy	0.02/0.025mm	
X/Z-axis repeatability(mm)	0.01/0.012mm	
X/Z axis fast feeding speed	8/10 M/MIN	
Tailstock sleeve travel	150mm	
Tailstock taper	MT5	
Dimension	2410/2660/3160 ×1560×1730mm	
Net weight	2800/3200/3500kg	

Standard configuration:

CK6150B China high quality automatic cnc metal turning lathe machine for sale

- 1.GSK928 CNC Controller 2.3 jaw manual chuck
- 3.4 electric tool holder
- 4.Auto lubrication system
- 5.lighting system
- 6.cooling system
- 7.one-piece bed casting
- 8.manual tailstock

Optional configuration

- 1.Siemens,Fanuc cnc controller system
- 2.pneumatic chuck,hydraulic chuck
- 3.pneumatic tailstock,hydraulic tailstock
- 4.6 station tool turret,8station tool turret
- 5.Auto feeder system
- 6.Chip conveyor
- 7.Centre -rest
- 8.Follow-rest



shandong lu young machinery co.,ltd

☎ 86 18660852746

✉ sales@luyoungmachinery.com

🌐 luyoungcncmachines.com

Room 1061, Building A, Guoshan Center, Taiqian Street, Taishan District, Taian City, Shandong Province