

## BT40 10000rpm Spindle 5 Axis Vertical Milling Center Vmc1580 Vertical Machining Center

### **Basic Information**

Place of Origin: CHINA
Brand Name: luyoung
Certification: CE
Model Number: vmc1580
Minimum Order Quantity: 1/SET

• Price: \$36900-\$49000

Packaging Details: Non-fumigating wooden cases

• Delivery Time: 30DAYS

Payment Terms: T/T, Western Union, MoneyGram, D/A, D/P

• Supply Ability: 10/SET



### **Product Specification**

Core Components: Motor, PLC, Gearbox

• Table Size: 1600\*800mm

• Year: 2024

Machine Color: As Your Requirement

Color: Customized According To Customer

Requirements

• Z Motor Torque: 7.7N.m

Port: Qingdao Or Shanghai Port

Keyword: Cnc Milling MachineKey Selling Points: High Productivity

• Product Type: Cnc 3/4/5 Axis Machine

Cnc Or Not: CNC
 Spindle Inner Cone: BT40/50
 Atc Type: Armless /arm

Application: VERTICAL Milling Machine



### More Images







### **Product Description**

BT40 10000rpm Spindle 5 Axis Vertical Milling Center Vmc1580 vertical machining center

# vmc1580 BT40-BT50 Items 3-Phase Power Requirement CNC Milling Machine in Any Color



### се

### Specification

| Item                                    | VMC1580  |
|---|----------|
| Size of worktable(length×width) mm      | 1700*800 |
| T slot (mm)                             | 5-22x150 |
| Max loading weight on worktable         | 1500     |
| X-Axis travel(mm)                       | 1500     |
| Y-Axis travel(mm)                       | 800      |
| Z-Axis travel(mm)                       | 700      |
| Distance between spindle nose and table | 170-840  |

| Distance between spindle center and column(mm) | 810   |  |  |  |
|--|---|--|--|--|
| Spindle taper                                  | BT50-155  |  |  |  |
| Max. spindle speed( rpm)                       | 8000/10000/12000  |  |  |  |
| Spindle motor power(Kw)                        | 18.5kw  |  |  |  |
| Rapid feeding speed:<br>X,Y,Z axis m/min       | 16/16/16 (24/24//24 liner guidway)                                      |  |  |  |
| Fast cutting speed m /min                      | 10m/min   |  |  |  |
| Positional accuracy                            | ±0.01 mm  |  |  |  |
| Repeat positional accuracy                     | ±0.005mm  |  |  |  |
| Auto Tool changer type                         | 16 tools head type tool changer(optional 24 arm type auto tool changer) |  |  |  |
| Max. tool length                               | 300mm   |  |  |  |
| Max. Tool diameter                             | Φ80(adjacent tool)/φ150(not adjacent tool)                              |  |  |  |
| Max.tool weight                                | 8kg   |  |  |  |
| Tool changing time(tool-to-tool)               | 7sec  |  |  |  |
| Air pressure                                   | 0.6 Mpa   |  |  |  |
| Machine weight                                 | 13000KG   |  |  |  |
| Overall sizse(mm)                              | 4300*3200*3100  |  |  |  |

### **Product Description**

The VMC1580 Main Functions of CNC Vertical Machining Center CNC vertical machining center use popular inverted T-shape column structure, it is morden machine tool with automatic tool changer and 3/4-axis CNC system. Continous & automatic milling, drilling, expanding, hinges and tapping on 4 surfaces' machining processes after once clamped, suitable for medium batch process all kinds of flat surface, hole, complicated surfaces machining. Saving processes, shorten production cycle, improved processing accuracy, it is the ideal machining equipment for automobile; construction mechanical; air; aerospace; military lines.

| Products feature  |
|---|
| Main Features of <b>vmc1580</b> 1. Rigid base with integral structure adopted 2. Good durability with cast iron machine bed made through super audio quenching 3. Good dynamic performance with advanced guide rail laminating technology 4. High precision, high-rigidity spindle, high speed 5. Sufficient precise lubrication with automatic lubrication system 6. Row knife structure which can change knifes very fast, high positioning accuracy and simple maintenance 7. Wide range of machining products due to the travel distance of X direction is up to 270mm and variety of knife tools can be installed on the machine tool 8. Spring chuck with high accuracy and high efficiency 9. Good protection function with fully-closed safe glass window 10. Modular design and optional accessories available on customer's needs |
| Company Profile   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |

| quality purpose, is the pursuit of all employees of our company, is also the guarantee of the majority of users' trust. |  |  |  |  |  |  |  |
|---|--|--|--|--|--|--|--|
| Packing & Delivery  |  |  |  |  |  |  |  |
|   |  |  |  |  |  |  |  |
|   |  |  |  |  |  |  |  |
|   |  |  |  |  |  |  |  |
|   |  |  |  |  |  |  |  |
|   |  |  |  |  |  |  |  |
|   |  |  |  |  |  |  |  |
|   |  |  |  |  |  |  |  |
|   |  |  |  |  |  |  |  |
|   |  |  |  |  |  |  |  |
|   |  |  |  |  |  |  |  |
|   |  |  |  |  |  |  |  |
|   |  |  |  |  |  |  |  |
|   |  |  |  |  |  |  |  |
|   |  |  |  |  |  |  |  |
|   |  |  |  |  |  |  |  |
|   |  |  |  |  |  |  |  |
|   |  |  |  |  |  |  |  |
|   |  |  |  |  |  |  |  |
|   |  |  |  |  |  |  |  |
|   |  |  |  |  |  |  |  |
|   |  |  |  |  |  |  |  |
|   |  |  |  |  |  |  |  |
|   |  |  |  |  |  |  |  |
|   |  |  |  |  |  |  |  |
|   |  |  |  |  |  |  |  |
|   |  |  |  |  |  |  |  |
|   |  |  |  |  |  |  |  |
|   |  |  |  |  |  |  |  |
|   |  |  |  |  |  |  |  |
|   |  |  |  |  |  |  |  |
|   |  |  |  |  |  |  |  |
|   |  |  |  |  |  |  |  |
|   |  |  |  |  |  |  |  |
|   |  |  |  |  |  |  |  |

- 1. The warranty period of our products is one year. If there is any damage in the warranty period, we will send it to you for free.We provide 24-hour online technical service and contact us at any time.
- 2. 365 days without false service, uninterrupted supply, pre-sales consultation, after-sales service and other technical support We also offer free technical training and overseas services.

#### Welcome to visit our factory



Room 1061, Building A, Guoshan Center, Taiqian Street, Taishan District, Taian City, Shandong Province